

SAFETY DATA SHEET

According to
HSNO Hazardous Substances (Safety Data Sheets) Notice 2017

Section 1. Identification of the material and the supplier

Product: **Fomtec FP 3% UL**
 Product Use: Appliance protection
 Restriction of Use: Refer to Section 15

New Zealand Supplier: **PSL Fire & Safety**
 Address: 10 Akatea Rd,
 Glendene
 Auckland 0602

Telephone: +64 9 818 8048
 Fax: +64 9 818 4484
 Email: sales@pslfireandsafety.co.nz

Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS: 5 June 2018 – Rev 3

Section 2. Hazards Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval No: Fire Fighting Chemicals – HSR002573

Signal Word: **Warning**

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
6.3B	H316	Causes mild skin irritation.	Skin Irrit. 3

Prevention Code	Prevention Statement
P103	Read label before use.

Response Code	Response Statement
P332 + P313	If skin irritation occurs: Get medical advice/ attention.

Storage Code	Storage Statement
None allocated	

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Iron (II) sulfate	1-2	7720-78-7
2-Methylpentane-2,4-diol	2-7	107-41-5
Non hazardous	To bal	

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for 15 minutes. If eye irritation persists: Get medical advice.
If on Skin	Remove contaminated clothing and wash before reuse. Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention.
If Swallowed	Wash out mouth thoroughly with water. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek medical attention if needed.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion:	Not applicable
Inhalation:	Not applicable
Skin:	Causes mild skin irritation.
Eye:	Not applicable.

Section 5. Fire Fighting Measures

Hazard Type	Non Flammable
Hazards from combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gasses or vapours.
Suitable Extinguishing media	This product is not flammable.
Precautions for firefighters and special protective clothing	Protective equipment for fire fighters.
HAZCHEM CODE	None Allocated

Section 6. Accidental Release Measures

Wear protective gear as detailed in Section 8. Avoid contact with eyes and skin. Do not breathe fumes.

Avoid discharge of larger quantities to drains.

Absorb with sand or other inert absorbent. Flush area clean with lots of water. Be aware of

potential for surfaces to become slippery.

Dispose of waste according to the applicable local and national regulations.

Section 7. Handling and Storage

Precautions for Handling:

- Read label before use.
- Do not breathe fumes or vapours.
- Wash hands thoroughly after handling.
- Avoid contact with eyes and skin.
- Wash contaminated areas with water and soap after finished work.
- Container must be kept tightly closed.
- Wear personal protective equipment as detailed in Section 8.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Keep container tightly closed.
- Store at specified temperature.
- Protect from direct sunlight.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA	STEL
	ppm mg/m ³	ppm mg/m ³
Hexylene glycol [107-41-5]	Ceiling 25 ppm (121 mg/m ³)	

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WES-STEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

Engineering Controls

Ensure adequate ventilation.

Personal Protection Equipment



Eyes	Use approved safety goggles or face shield.
Hands	Protective gloves must be used if there is a risk of direct contact or splash. Rubber or plastic is recommended.
Skin	Use protective clothing which covers arms and legs.
Respiratory	Under normal conditions of use respiration protection should not be required.

Section 9 Physical and Chemical Properties

Appearance	Liquid
Colour	Dark coloured
Odour	Characteristic
Odour Threshold	Not available

pH	6.0 – 7.0
Boiling Point	Not available
Melting Point	Not available
Freezing Point	~-15°C
Flash Point	Not available
Flammability	Not available
Upper and Lower Explosive Limits	Not available
Vapour Pressure	Not available
Vapour Density	Not available
Specific Gravity	~1.160 g/ml
Solubility	Completely soluble in water.
Partition Coefficient:	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	≤30 mPas (method: Brookfield DV)
Particle Characteristics	Not available

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous reactions	None known.
Conditions to Avoid	Earth metals such as sodium, potassium and barium.
Incompatible Materials	Alkali earth metals.
Hazardous Decomposition Products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gasses or vapours.

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Not applicable.
Skin	Causes mild skin irritation.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Section 12. Ecotoxicological Information

This product is not hazardous to the environment.

Product:

	Value	Method of testing	Species	Duration
Acute aquatic, fish	>1000mg/l		Leuciscus Idus	96h

Persistence and degradability	Value: > 90, Test period: 28days. The product is expected to be biodegradable.
Bioaccumulation	Is not expected.
Mobility in Soil	The product contains substances, which are water soluble and may spread in water systems.
Other adverse effects	No data available

Section 13. Disposal Considerations

Disposal Method: Triple rinse and dispose of according to Local regulations.

Precautions or methods to avoid: None known.

Section 14 Transport Information

This product is NOT classified as a Dangerous Good for transport in NZ ; NZS 5433:2012

Section 15 Regulatory Information**New Zealand:**

This substance is classified as hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Fire Fighting Chemicals – HSR002573

HSNO Classification: 6.3B

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	Not required
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	Not required
Emergency Response Plan	Not required
Secondary Containment	Not required
Restriction of Use	Only use for the intended purpose.

Section 16 Other Information**Glossary**

EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.

TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact PSL Fire & Safety, if further information is required.

Issue Date: 5 June 2018 Review Date: 5 June 2023