


Suction Hose

The PVC Plasticised hose has an incorporated spiral reinforcement of anti-shock rigid PVC. The inside surface is smooth and the outside is a light corrugate surface. Hose is coupled with stainless steel ferrules for both the 100mm and 75mm suction hose



SKU:023900

FEATURES:

- Very Strong
- Resistant to crushing
- Resistant to abrasion, atmospheric agents and most chemicals
- Temperature rated $-10^{\circ}\text{C} + 60^{\circ}\text{C}$

75mm clear suction

2.4 Metre with Storz coupling - SKU 60247
3.6 Metre with Storz Coupling - SKU 60248
2.4 Metre with Camlock Coupling - SKU 60249
3.6 Metre with Camlock Coupling - SKU 60250

100mm clear suction

2.4 Metre with Storz coupling - SKU 60245
3.6 Metre with Storz Coupling - SKU 60426

Foot Valve

The Firemaster foot valve is manufactured in a heavy duty PVC. This unit is a combination foot valve and strainer for use with suction hose coupled with 50mm MBSP. The spring loaded valve ensures instantaneous closing. Dismantles easily for cleaning and maintenance.



SKU:8000

Suction Strainers

75mm round thread (SKU:053000)
100mm round thread (SKU:053100)
100mm round thread low level (SKU:053200)
140mm round thread (SKU:053300)



3000

Basket Strainer & Skirt

75 mm (SKU:7208)
100 mm (SKU:7209)
140 mm (SKU:7211)
50 mm (for Wajax Forestry Pump) (SKU:7213)



7213

