

# STANDARD LANDING VALVE

## Features

- Gun Metal construction body manufactured to BS5041-1
- Glands are forged brass
- Flanges steel galvanised painted red
- Ductile Iron 140mm hand wheel,
- Aluminium adaptors and blank caps
- Recommended operating pressure is 1600kPa max
- Option of single lever outlet or single twist 70mm female
- instantaneous aluminium coupling.

### 70 mm SINGLE LEVER OUTLET:

Gunmetal 65mm (2½") MBSP Thread (SKU:60240)

Gunmetal 65mm (2½") Table D Flange (SKU:60241)

### 70mm SINGLE TWIST OUTLET:

Gunmetal 65mm (2½") MBSP Thread (SKU:60242)

Gunmetal 65mm (2½") Table D Flange (SKU:60243)

The PSL Standard Landing Valves are a water fire fighting system suitable for any position where they are required to be installed in public view. Suitable for firefighting in plants, schools, hotels and in mines etc.

PSL offer the range of STANDARD quality landing valves that fits between the Industrial and Premier range. Whilst not to the same presentable quality as our Premier range, our Standard range still offer excellent value for performance with very little difference in the aesthetics



[www.pslfireandsafety.co.nz](http://www.pslfireandsafety.co.nz)

+64 9 818 8048  
[sales@pslfireandsafety.co.nz](mailto:sales@pslfireandsafety.co.nz)



Quality Management System Certification  
ISO 9001:2015



Environmental Management System Certification  
ISO 14001:2015



Occupational Health and Safety Management System Certification  
ISO 45001:2018